

1/4




Fig. 1

2/4




Fig. 2

114

```

int* intPtr;
int proc1 ();

inline void proc2 (int* i) {
    (*i)++;      ← S3
}
int proc3 () {
    int a;
    a= proc1 (); ← S1
    proc2 (&a);  ← S2
    *intPtr = 1; ← S4
    return (a);  ← S5
}

```

Fig. 3

3/4

115

```
@S1 a = proc1 ();
CALL proc1 //Call procedure 'proc1'
STR a      //Store return value into 'a'
@S2 proc2(a);
LDA a      //Load address of 'a'
STR i      //Store address of 'a' into inline parameter 'i'
@S3 (*i)++;
LOD i      //Load 'i'
IND int*   //Load integer value pointed to by 'i' (indirect load of 'a')
INC 1      //Increment value
LOD i      //Load 'i'
STO int*   //Store increment integer value at location pointer to by 'i'
              (indirect store to 'a')
@S4 *intPtr = 1;
LOD 1      //Load value 1
LOD intPtr //Load 'intPtr'
STO int*   //Store 1 at location pointed to by 'intPtr'
@S5 return (a);
LOD a      //Load 'a'
RET        //Return
```

Fig. 4

115

```
@S1 a = proc1 ();
CALL proc1 //Call procedure 'proc1'
STR a      //Store return value into 'a'
@S3 (*i)++;
LOD a      //Load 'a'
INC 1      //Increment value
STR a      //Store incremented value into 'a'
@S4 *intPtr = 1;
LOD 1      //Load value 1
LOD intPtr //Load 'intPtr'
STO int*   //Store 1 at location pointed to by 'intPtr'
@S5 return (a);
LOD a      //Load 'a'
RET        //Return
```

Fig. 6

Fig. 5

